### Model Workflow

Amy Langenhorst Summer School 2012

- Intro to FMS and FRE
- Workflow Basics
- FRE Features and Components
- FRE Job Streams
- FRE Archived Output
- FRE Utilities
- FRE XML Overview

## Flexible Modeling System


 FMS is a software framework which provides infrastructure and interfaces to component models and multi-component models.

Coupler Layer

Model Layer

Distributed Grid Layer


Machine Layer



- Development timelines:
  - Component models by scientific group, continuous
  - Annual FMS city releases, 200+ configurations tested

# Flexible Modeling System


 FMS is a software framework which provides infrastructure and interfaces to contract models and multi-component models



- Development timelines:
  - Component models by scientific group, continuous
- Annual FMS city releases, 200+ configurations tested


#### **FMS** Runtime Environment

 FRE is a set of workflow management tools that read a model configuration file and take various actions.



### FMS Runtime Environment

 FRE is a set of workflow management took that read a model configuration file and take with actions.



- Intro to FMS and FRE
- Workflow Basics
- FRE Features and Components
- FRE Job Streams
- FRE Archived Output
- FRE Utilities
- FRE XML Overview

#### Workflow

- A workflow is a comprehensive but precise description of a sequence of actions
  - reproducibility
  - perturbations
  - differencing
  - error handling: user level & system level
- A typical workflow of CM2.5, one of our larger climate models, uses 1.6 million core hours and produces 13 TB of data in the course of a 100 year run.


#### Climate Model Workflow

- Source code version control
- Model configuration management
- Building executables
- Control of model execution
- Monitoring (job level and model level)
- Post-processing
- Archiving
- Automated analysis
- Entry into curator database

## Post-processing Defined

- Preparing diagnostic output for analysis
  - Time series
    - Hourly, daily, monthly, seasonal, annual
  - Climatological averages
    - For example, an average of ten Januaries
  - Horizontal interpolation: cubed sphere data can be regridded to lat-lon
  - Vertical interpolation: pressure levels
  - Hooks to call user scripts to create plots or perform further data manipulation
  - Enter the model into the curator database

## Components and Grids



- Intro to FMS and FRE
- Workflow Basics
- FRE Features and Components
- FRE Job Streams
- FRE Archived Output
- FRE Utilities
- FRE XML Overview

#### **FRE Features**

- Encapsulated support for multiple sites
  - compiler, batch scheduler, utility paths, user defaults
  - simple: a linux workstation
  - complex, parallel and distributed: remote computing on a 100,000 processor Cray at ORNL with local data archiving and post-processing
- Model component-based organization
- Integrated model testing
- Experiment inheritance for perturbations
- Standard post-processing functions and user-level functions

### FRE Workflow Components


- XML Model Description File
  - contains a complete description of one or more experiments
- Command line utilities read XML file
- Site configuration files
  - -script templates
  - standards and conventions for file names and locations
- FRE version management with environment modules

- Intro to FMS and FRE
- Workflow Basics
- FRE Features and Components
- FRE Job Streams
- FRE Archived Output
- FRE Utilities
- FRE XML Overview


#### FRE Job Stream Overview

- Experiments run in segments of model time
  - -Segment length is user-defined
  - More than one segment per main compute job is possible
- After each segment:
  - -the state is saved
  - data is transferred to long term storage
  - a number of post-processing jobs may be launched to operate on the data in parallel

## Flow Through The Hardware



FRE Job Stream
Two-segment job with post-processing in **chained** mode



- Intro to FMS and FRE
- Workflow Basics
- FRE Features and Components
- FRE Job Streams
- FRE Archived Output
- FRE Utilities
- FRE XML Overview

## **Archived Output**

```
/archive/$USER/fre/CM2.1U Control-1990 E1.M 3A
  - ascii
   restart
  - history
   pp
       atmos
             -- monthly
                `-- 5yr
                     -- atmos.000101-000512.mon.nc.cpio
                     -- atmos.000601-001012.mon.nc.cpio
            av
            `-- monthly 5yr
                 -- atmos.0001-0005.01.nc
                 -- atmos.0001-0005.02.nc
```

- Intro to FMS and FRE
- Workflow Basics
- FRE Features and Components
- FRE Job Streams
- FRE Archived Output
- FRE Utilities
- FRE XML Overview

#### FRE Utilities

fremake: obtain code, create/submit compile scripts

frerun: create and submit run scripts

frepp: create and submit post-processing scripts

frelist: list info about experiments in an xml file

frestatus: show status of batch compiles and runs

frecheck: compare regression test runs

frepriority: change batch queue information

freppcheck: report missing post-processing files

refrepp: submit jobs to generate missing pp files

frescrub: delete duplicate post-processing files

freconvert: convert XML to a newer version

fredb: interact with Curator Database

- Intro to FMS and FRE
- Workflow Basics
- FRE Features and Components
- FRE Job Streams
- FRE Archived Output
- FRE Utilities
- FRE XML Overview

## Sample XML: Setup

```
<experimentSuite>
 <setup>
   <platform name="qfdl.default">
    <directory stem="subdirectory/paths"/>
    <csh>
      module load intel
      module load fre
    </csh>
    property name="FMS ARCHIVE ROOT"
               value="/archive/fms"/>
   </platform>
 </setup>
 <experiment name=""> ...
```

## Sample XML: Experiment

```
<experiment name="CM2.5A 2" inherit="CM2.5">
 <component name="fms">
   <source vc="cvs" root="/home/fms/cvs">
    <codeBase version="riga">shared</codeBase>
    <csh>
      cvs up -r riga arl shared/.../file
    </csh>
   </source>
   <compile>
    <cppDefs> -Duse netCDF </cppDefs>
   </compile>
 </component>
 <component name="mom4p1"> ...
```

## Sample XML: Input

```
<input>
 <namelist name="vert diff driver nml">
   do conserve energy = .true.
 </namelist>
 <dataFile label="input" target="INPUT/"</pre>
            chksum="" size="" timestamp="">
   $(FMS ARCHIVE ROOT)/am2/cover type field
 </dataFile>
 <diagTable>
     diagnostic variable table
 </diagTable>
</input>
```

## Sample XML: Runs and Jobs

```
<runtime>
 cproduction simTime="26" units="years"
              npes="120" runTime="12:00:00">
   <segment simTime="12" units="months"</pre>
             runTime="06:00:00"/>
 </production>
 <regression name="basic">
   <run days="8" npes="60" runTime="00:15:00">
 </regression>
 <dataFile label="reference">
   $(FMS ARCHIVE ROOT)/am2/riga/19950108.tar
 </dataFile>
</runtime>
```

## Sample XML: Postprocessing

```
<postProcess>
 <component type="atmos" source="atmos month"</pre>
      cubicToLatLon="90,144" zInterp="era40">
   <timeSeries freq="monthly"
                chunkLength="10yr">
     <variables> precip, temp </variables>
     <analysis script="/home/template.csh"/>
   </timeSeries>
   <timeAverage source="monthly"
                 interval="10yr"/>
 </component>
</postProcess>
```

### Questions?

For more details on FRE, see:
 <a href="http://www.gfdl.noaa.gov/fms-fre-usage">http://www.gfdl.noaa.gov/fms-fre-usage</a>

